

HR600

LARGE AREA ROTARY MOWER



- **LOW MAINTENANCE, DIRECT DRIVE HYDRAULIC DECKS**
- **TILT SENSOR TECHNOLOGY (TST) WARNS OF UNSAFE WORKING ANGLE**
- **LOW WEIGHT FOR EFFICIENCY AND FUEL ECONOMY**

CUT WIDTH
137"
(3.5M)

CUT HEIGHT
1" - 4.75"
(25MM - 121MM)
0.25" (6.4MM)
INCREMENTS

CUTTING CAPACITY
13.8 AC
(5.6HA) / HR
AT 10MPH (16KM/H)

FUEL CAPACITY
20.4 GAL
(77.1L)

MOWER ENGINE
KUBOTA®
65.2HP
(48.6KW) TURBODIESEL

TRANSPORT SPEED
15.5 MPH
(25KPH)

The HR600 large area rotary mower lets you take Jake's power anywhere. It cuts roughs, surrounds, around obstacles on golf courses, parks and sports fields effortlessly in all conditions. Fitted with MARBAIN® Boron Alloy Steel Blades, it will give you a first-class finish everytime.

Tilt Sensor Technology, will also warn you of safe working angles. The HR600 is low weight for efficiency and fuel economy, combined with zero maintenance decks and unrivalled operator comfort, it will keep you mowing until the work is done.



SINCERELY

Jake

For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946



Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.

© 2021 Textron Specialized Vehicles Inc.

HR600

LARGE AREA ROTARY MOWER



ISO mounted operator platform for comfortable, productive ride

Q Amp® variable rate steering system

Cruise control & adjustable travel speeds

Low-maintenance decks means less time greasing & no belt adjustments

Lightweight durable deck pan design made from high strength steel

Foldable ROPS as standard

Hydraulically driven, temperature controlled reversing fan

Easy-access service bay

SureTrac™ 4WD parallel-cross-series traction system

Generous ground clearance

Maintenance free wet parking brakes



Low maintenance, direct drive hydraulic decks



Operator lift lower controls & onboard diagnostics



Trustworthy Kubota® engine & cooling reversing fan

DECKS & CUTTING UNITS

NUMBER AND SIZE	1 x 60" (1.52m) front deck; 2 x 44" (1.12m) wing units
BLADE MATERIAL	MARBAIN® boron alloy steel
DECK LIFT & LOWER	Individual via fingertip operated joysticks
WEIGHT TRANSFER	On demand electrically operated hydraulic weight transfer system
DECK CONSTRUCTION	11 gauge (3mm) Strenx, high strength steel shell

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Hydrostatic closed loop parallel-cross-series SureTrac™ system
DECK DRIVE	Seven individual hydraulic motors with self lubricating integral bearings
HYDRAULIC SYSTEM	13.3 gal. (50.2L) reservoir with 10 micron remote charge filters and suction screening at tank. Oil cooler in side by side radiator.
SERVICE BRAKES	Dynamic through hydrostatic traction system
PARKING BRAKES	Automatic wet parking brakes integrated into wheel motors
STEERING	Power Steering
MOWING SPEED	10mph (16.4km/h)
REVERSE SPEED	4mph (6.4km/h)

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	3900lbs (1769kg), 4356lbs (1976kg) with cab
LENGTH (less catchers)	143" (3.62m) front deck down
OVERALL HEIGHT (ROPS up)	83" (2.1m)
WHEELBASE	64" (1.65m)
TRANSPORT WIDTH	65" (1.67m)
WORKING WIDTH	143" (3.63m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- Road light kit
- Canopy/sunshade
- Climate controlled cab
- Cab accessories - road light kit, Rear wiper kit